ZHUOTAI SANITARY WARE CO., LTD.



PRODUCT DESCRIPTION

Offering natural-looking LED light for the vanity and ceiling, while bathing the room with radiant wall-glow light, the **Braga** provides a novel approach to both form and function.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forwardfacing task lighting as well as top and bottom wall-glow ambient lighting. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using replaceable LEDs with a greater than or equal to 90 CRI (color rendering index). Product will be made in China with best quality components and have a 5year limited warranty.

THE ZHUOTAI MIRROR ADVANTAGE

- ✓ 22 years of mirror knowledge and expertise
- ✓ 10,000pcs installations every month
- \checkmark Premium quality you can buy with full confidence
- \checkmark Lowest total cost of ownership
- ✓ Quick ad professional customer service support
- ✓ 25,000-square-meter China manufacturing facility

FEATURES AND BENEFITS

- Lead-free, copper-free, corrosion-resistant glass
- Forward-facing task lighting
- Wall-glow ambient lighting on top and bottom with diffuser for a finished side view
- Suitable for damp bathroom environments
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- 5-year limited warranty
- Made in China with best quality components

AVAILABLE OPTIONS

- Defogger
- CCT: 2,700K
- 10%-100% brightness dimming
- Forward-phase dimming
- Custom sizes

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- CRI: 90+
- CCT: 3,000K, 4500K, 6500K
- 60 initial lumens/inch
- Maximum 100 lumens/watt efficacy
- Calculated 52,000-hour LED lifespan

SAFETY SPECIFICATIONS

- Entire assembly meets CE, IP57, RoHs, ErP, UKCA international certifications
- Safety-backed mirror

INSTALLATION SPECIFICATIONS

- 12V LED driver, Input 220V-240V hardwire electrical connection;
- Mirror will be hung on the bracket fixed on wall, all fittings including
- Controlled by touch switch on mirror
- Installation wiring may be different on mirrors equipped with additional options
- Fixture can only be hung in the WxH orientation as shown; fixture is not field-interchangeable

MODELS

Base Model*	Dimensions	Power Requirements
BRAGA42-24.00x36.00	24"W x 36"H x 1.75"D (610mm x 914mm x 44mm)	INPUT 220-240V, OUTPUT 12V 38W
BRAGA42-30.00x36.00	30"W x 36"H x 1.75"D (762mm x 914mm x 44mm)	INPUT 220-240V, OUTPUT 12V 43W
BRAGA42-36.00x36.00	36"W x 36"H x 1.75"D (914mm x 914mm x 44mm)	INPUT 220-240V, OUTPUT 12V 57W
BRAGA42-48.00x36.00	48"W x 36"H x 1.75"D (1219mm x 914mm x 44mm)	INPUT 220-240V, OUTPUT 12V 75W
BRAGA42-60.00x36.00	60"W x 36"H x 1.75"D (1524mm x 914mm x 44mm)	INPUT 220-240V, OUTPUT 12V 96W

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

